

# ACI

VOL. 108, NO. 1  
JANUARY-FEBRUARY 2011

# MATERIALS JOURNAL

- 3 High-Early-Strength Engineered Cementitious Composites for Fast, Durable Concrete Repair—Material Properties/*M. Li and V. C. Li*
- 13 Unified Shrinkage Model for Concrete from Autogenous Shrinkage Test on Paste with and without Ground-Granulated Blast-Furnace Slag/*Y. Wei, W. Hansen, J. J. Biernacki, and E. Schlangen*
- 21 Evaluation of Autogenous Deformation of Concrete at Early Ages/*S. Slatnick, K. A. Riding, K. J. Folliard, M. C. G. Juenger, and A. K. Schindler*
- 29 Influence of Surface Crack Width on Bond Strength of Reinforced Concrete/*D. Tang, T. K. C. Molyneaux, D. W. Law, and R. Gravina*
- 38 Simple Analytical Model for Formwork Design of Self-Consolidating Concrete/*J. Hong Kim, M. W. Beacraft, S. H. Kwon, and S. P. Shah*
- 46 Ultra-High Performance Concrete with Compressive Strength Exceeding 150 MPa (22 ksi): A Simpler Way/*K. Wille, A. E. Naaman, and G. J. Parra-Montesinos*
- 55 Prediction of Efficiency Factor of Ground-Granulated Blast-Furnace Slag of Concrete Using Artificial Neural Network/*B. Boukhatem, M. Ghrici, S. Kenai, and A. Tagnit-Hamou*
- 64 Engineering Properties of Alkali-Activated Natural Pozzolan Concrete/*D. Bondar, C. J. Lynsdale, N. B. Milestone, N. Hassani, and A. A. Ramezani-pour*
- 73 Effectiveness of Mixing Time on Hardened Properties of Waterglass-Activated Slag Pastes and Mortars/*M. Palacios and F. Puertas*
- 79 Failure Behavior of Concrete Cylinders under Different End Conditions/*M. Roddenberry, R. Kampmann, M. H. Ansley, N. Bouchard, and W. V. Ping*
- 88 Prediction of Equivalent Steady-State Chloride Diffusion Coefficients/*P. Ghosh, A. Hammond, and P. J. Tikalsky*
- 95 Damage Behavior of Yarn Embedded in Concrete Using Acoustic Emission Analysis/*B.-G. Kang, J. Hannawald, and W. Bramehuber*

A JOURNAL OF THE AMERICAN CONCRETE INSTITUTE



American Concrete Institute®  
Advancing concrete knowledge